

Product Data Sheet

GWA1512


Wireless devices



A system of command and control wireless devices based on Zigbee technology that offers innovative solutions for the renovation of buildings, minimizing the structural interventions. Zigbee is a safe and reliable system because the data exchanged are encrypted and every node of the network always ensures reachability among all the devices (mesh network). The Zigbee devices enrich the range of home&building automation solutions by Gewiss and can be managed via App, with smartphone and tablet, through the Smart Gateway.

Category	Smoke alarm	Colour	White
Communication protocol	Zigbee (IEEE 802.15.4)	Supply voltage	Battery powered
Power supply batteries	CR123 replaceable	Output power	8 dBm
Siren output	85 dB/3 m	Temperature sensor	050 °C
Standard	2014/53/EU, EN 60669-2-1, ETSI EN 300 328, EN 14 604	IP degree	IP20
Working temperature	0 ÷ +50 °C	Stocking temperature	-20 ÷ +80 °C
Relative humidity (non-co	ndensative) 10 ÷ 95%	Dimensions (mm)	Ø 65x40
Electrocod	051A		

DIMENSIONAL



TECHNICAL SYMBOLOGY



IP20

STANDARDS/APPROVALS







GEWISS S.p.A. Via A. Volta, 1 24069 Cenate Sotto - Bergamo - Italy tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com sat@gewiss.com Last update 07/12/2020 Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice